


# Data sheet

Part No.	<b>HFPRM LG 3M</b>
Description	rigid insulating conduit with turbo grooves, halogenfree, plain, with moulded-on coupler  medium compression resistance, medium impact resistance
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating
Classification	33431
Compression resistance	> 750 N



Standard: EN 61386-1, EN 61386-21, EN 60754, EN 50642, EN 61034



Compressive strength class	Impact strength	Operating temperature	Bending strength
Medium (class 3)	Medium (class 3)	-25 to +105 °C	Rigid

Art. No.	ED	ID	VPE small/medium/large
087223	16 mm	11,1 mm	3 m / 111 m / 6216 m
087224	20 mm	15 mm	3 m / 111 m / 3996 m
087225	25 mm	20 mm	3 m / 57 m / 2280 m
087226	32 mm	26,7 mm	3 m / 57 m / 1368 m
098784	40 mm	34 mm	3 m / 21 m / 966 m
098785	50 mm	43,5 mm	3 m / 21 m / 630 m
098786	63 mm	55,5 mm	3 m / 21 m / 378 m

## Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	True
Suitable for subsurface installation (screed)	True
Outdoor installation	True
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

## Further technical details

Details	
Halogen free	True
With sleeve	True
Fire retardant version	True
Material	PP-Blend

Cardboard packaging used is made from 100% waste paper and is fully recyclable,  
plastic packaging is fully recyclable.