


Data sheet

Part No.	HFXP-HT BK
Description	pliable conduit, halogen-free, corrugated medium compression resistance, medium impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	33552
Compression resistance	> 750 N

Standard: EN 61386-1, EN 61386-22, EN 60754, EN 50642, EN 61034



Compressive strength class	Impact strength	Operating temperature	Bending strength
Medium (class 3)	Medium (class 3)	-45 to +150 °C	Pliable

Art. No.	ED	ID	Bending radius	PU	PU
016574	13 mm	9 mm	84 mm	50 m	4500 m
011301	16 mm	9,9 mm	112 mm	50 m	2700 m
011302	20 mm	13,9 mm	140 mm	50 m	2700 m
011303	25 mm	18 mm	175 mm	50 m	1600 m
011304	32 mm	23,5 mm	224 mm	25 m	675 m
013254	40 mm	30 mm	280 mm	25 m	500 m
013255	50 mm	38,5 mm	350 mm	25 m	300 m
019897	63 mm	54 mm	441 mm	25 m	175 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	False
Machine and systems installation	True
Suitable for subsurface installation (screed)	False
Outdoor installation	False
Suitable for installation on wood	True
Hollow wall	True
Underground installation	False

Further technical details

Details	
Halogen free	True
With sleeve	False
Fire retardant version	True
Material	PC-Blend

Cardboard packaging used is made from 100% waste paper and is fully recyclable,
plastic packaging is fully recyclable.